



MODEL 6

APPLICATIONS
 FEATURES
 OPTIONS
 SPECIFICATIONS

The PositionIt Model 6 unit is a versatile, compact positioning system ideal for heavier applications. It has a standard extension of 20 feet and a maximum capacity of 275 lbs. Its portable design features the optional COBRA system that provides your payload with self-contained power and control capability. The optional DMX control interface can be used to generate precise computer directed movements.

- | |
|---|
| <ul style="list-style-type: none"> ➤ Stage and Prop Lighting ➤ Commercial Lighting and Projection Systems ➤ Surveillance Cameras ➤ Displays, Trusses and Signs ➤ Residential Home Theaters, Outdoor Lighting |
| <ul style="list-style-type: none"> ➤ Pendant Up/Down Control ➤ Fleenor Designed DMX Interface ➤ Variable Speed Control ➤ Adjustable Upper and Lower Limit Heights |
| <ul style="list-style-type: none"> ➤ Dynamic Guy System ➤ COBRA System - Payload Cable Management (1-1/4 in maximum conduit ID) ➤ Battery Power Operation (12 or 24 VDC) |

Vertical Lift Capacity	
Upright	275 lbs [125 kg]
Inverted	450 lbs [204 kg]
Standard Extension*	20 ft [6 m]
Maximum Stroke Speed*	6 in/sec [15 cm/sec]
Power Requirements Specified Before Delivery	115 or 230 VAC
Motor HP	1 HP
Full Load Amps per Motor	10 Amps (115 VAC)
Base Unit Weight	350 lbs [159 kg]

* - Custom stroke speeds and extension lengths available

